



Welcome to



BANDO



PT. BANDO INDONESIA



Authorized Agent :

PT RANADITYO SUKSES MAKMUR

Jl. Bakti 4 Kav. 52, Cilandak Timur, Pasar Minggu, Jakarta Selatan 12560 - Indonesia

Phone : +62 21 7823856, 0855 808 5555

WA Chat : 0855 105 8888

Email : sales@ranadityo.co.id

ranadityo_suksesmakmur@yahoo.com

Website : www.ranadityo.co.id



COMPANY PROFILE



1906

In 1906 the first Bando factory was built in Kobe and since that start Bando



1987

Joint venture Bando Chemical Industries Ltd. Japan with PT. Kreasi Utama Investama



1995

Expanded to Conveyor Belt Productions

RUBBER LAGGING for DRUM PULLEY



Application

Rubber lagging at pulley surface to prevent slip



Features

Shape by molding



Range Product

Rubber Width : 1050 mm
Rubber thickness : 15 mm
Length : 1950 mm
Abrasion : < 250 mm³
Hardness : 55-65 JIS Type A

Type of Rubber Lagging :

- Diamond Lagging
- Chevron/Hering Bone Lagging
- Rib Lagging
- Flat/Plain Lagging

RUBBER LAGGING for DRUM PULLEY



DIAMOND LAGGING	CHEVRON/HERING BONE LAGGING	RIB LAGGING	FLAT/PLAIN LAGGING
Fabricated from high durometer material for abrasion resistance and offer superior tractive properties, water shedding, keep belt not slip, and protect against wear and corrosion.	Can offers the superior tractive in all pulley applications. Give a path to water or other liquid for escape. Solves wear problem, reduce slippage and protect against abrasive condition.	Help prevent belt slippage in extreme dirt condition. Horizontal groove trap can and defect water result superior coefficient of friction.	Suitable for any pulley where wtershield is not necessary, can increase lifetime of bell, protect the pulley against wear & corrosion.
Use Soft Natural Rubber RS, GC 58 (BI.S.RS) Impact resistant application for pulley lagging and skirt rubber Optional : standard to customer for dimension, crowned or machne finished, many material offers such as SBR (styrene butadine rubber), neoprene, EPDM (ethylene propylene diene M class)			

SKIRT RUBBER



Full Rubber



Application

Skirting Rubber to prevent spill out material



Features

Solid rubber and have a hardness lower than surface belt



Range Product

Rubber Width : 100 ~ 2.200 mm
Rubber thickness : 5 ~ 25 mm
Abrasion : max 400 mm³
Hardness : 53±5 JIS Type A

CONTACT US



Office and
Factory

PT BANDO INDONESIA

Jl. Gajah Tunggal, Kel. Pasir Jaya, Kec Jati Uwung
Tangerang 15135, Banten - Indonesia



Authorized
Agent

PT RANADITYO SUKSES MAKMUR

Jl. Bakti 4 Kav. 52, Cilandak Timur,
Pasar Minggu, Jaksel 12560 - Indonesia
Phone : +62 21 7823856, 0855 808 5555
WA Chat : 0855 105 8888

Email : sales@ranadityo.co.id
ranadityo_suksesmakmur@yahoo.com

Website : www.ranadityo.co.id